



Technical Specifications

APC Replacement Battery Cartridge with 2 Year Warranty

APC Easy UPS On-Line SRV Battery Pack (5/6/10kVA) for Extended Runtime Model 240V, 2160VAh, rackmount with kit, 3U



Nishant Power Solutions Pvt. Ltd.

55-54 4B, High Street Corporate Centre,
Kapurbawadi, Thane (W) MS India 400601

Tel : +91 22 25404025 / Cell 9820843000

Email : sales@upsbatteries.co.in Visit at : www.upsbatteries.co.in

Life Is On **Schneider**
Electric

Technical Specifications APC Replacement Battery Cartridge

Presentation	RV240RBP-9A / SRV240RBP-INX	SRV72RBP-9A / SRV72RBP-9A-INX	SRV120RLBP2-9A
Application	APC Easy UPS On-Line SRV Battery Pack (5/6/ 10kVA) for Extended Runtime Model 240V, 2160VAh, rackmount with kit, 3U	APC Easy UPS On-Line SRV 72V Battery Pack for 2/3KVA Extended Runtime Model India	APC Easy UPS On-Line SRV 120V RM Battery Pack for 15/20kVA Rack Extended Runtime Model
Main			
Product or component type	Battery	Battery	Battery
Number of rack unit	3U	2U	3U
Battery type	Lead-acid battery	Lead-acid battery	Lead-acid battery
Provided equipment	Documentation CD User manual Battery cable Rack mounting brackets	Documentation CD User manual Battery cable	Documentation CD User manual Battery cable Rack mounting brackets
Range of product	Smart-UPS Battery Systems	Smart-UPS Battery Systems	Easy UPS On-Line
Batteries & Runtime			
Number of battery blocks per string	20	6	20
Device mounting	Rack mount	Rack mount	Rack mount
Number of battery filled slots	0 Number of battery free slots	0 Number of battery free slots	0 Number of battery free slots
Battery voltage	240 V	72 V	+/- 120 V
Physical			
Colour	Black	Black	Black
Height	13.3 cm	8.6 cm	13.3 cm
Width	43.8 cm	43.8 cm	43.8 cm
Depth	60.6 cm	63.2 cm	68.6 cm
Net weight	63 kg	40 kg	64 kg
mounting mode	Rack-mounted with kit	Rack-mounted with kit	Rack-mounted with kit
USB compatible	No	No	No
Environmental			
Ambient air temperature for operation	0...40 °C	0...40 °C	0...40 °C
Relative humidity	0...95 % non-condensing	0...95 % non-condensing	0...95 % non-condensing
Operating altitude	0...3000 m	0...3000 m	0...3000 m
Packing Units			
Unit Type of Package 1	PCE	PCE	PCE
Number of Units in Package1	1	1	1
Package 1 Height	25 cm	24 cm	25 cm
Package 1 Width	87 cm	80 cm	58 cm
Package 1 Length	58 cm	60 cm	87 cm
Package 1 Weight	70 kg	45 kg	72 kg
Unit Type of Package 2	No	No	PAM
Contractual warranty			
Warranty	2 Years repair or replace	2 Years repair or replace	2 Years repair or replace

Nishant Power Solutions Pvt. Ltd.

55-54 4B, High Street Corporate Centre,
Kapurbawadi, Thane (W) MS India 400601
Tel : +91 22 25404025 / Cell 9820843000
Email : sales@upsbatteries.co.in Visit at : www.upsbatteries.co.in

