

EXIDE

**POWERSAFE
PLUS**

the technology within

POWERING THE
CYBER WORLD

INDUSTRIAL



Winner of EFY Awards for
Best SMF Battery... 10 times in a row
2005 - 2014



Sealed Maintenance Free VRLA Batteries

Visit us at: www.exide4u.com

Presenting NEW Improved Exide Powersafe Plus, Sealed Maintenance Free VRLA batteries with enhanced design features, which give a higher performance & reliability, better suited to Indian conditions. Exide Powersafe is a product of collaborative efforts of in-house R&D of Exide Industries Ltd., the largest lead-acid battery manufacturer of India and M/s. Shin-Kobe Electric Machinery Co., Japan, the makers of world renowned Hitachi batteries. No wonder it is approved by all major OEMs and Institutional customers and is considered to be the Power Pack of the future.

HIGHLIGHTS OF THE NEW PRODUCTS: ● ABS Container & Lid ■ Better aesthetics ■ Stronger and free from distortion ● Brass Terminal with Lead Coating ■ Better conductivity ■ Free from corrosion ● Over Partition Welding ■ Free from inter-cell weld failure ● Thicker Separator ■ More acid volume ■ Better capacity retention ■ Improved electrical performance

FEATURES: | New Improved Sealed Maintenance free | Free from Orientation Constraints | Eco-Friendly | Easy Handling and No Installation Constraints | Ready-to-Use | Long Service Life | Low Self-Discharge | Excellent Charge Retention and Recovering Ability | Superior High-Rate Discharge | High Reliability | Wide Range

APPLICATIONS: UPS System, Telecommunication Equipment, Fire Alarm & Security System, Office Automation Equipment, EPABX & Electronic Weighing Scale and in many other applications.

EP SERIES: Small and medium sized sealed lead acid battery performance characteristics conforming to JIS C8702.

Type of Battery	Nominal Voltage (V)	Rated Capacity (Ah) at 27 deg C						Dimensions (mm)				Weight (Kg) (+/-5%)
		20 hrs. 1.75 VPC	10 hrs. 1.75 VPC	3 hrs. 1.7 VPC	1.5 hr 1.7 VPC	1 hr 1.6 VPC	30min 1.6 VPC	Overall Height ±2	Height up to lid top ±2	Length ±1	Width ±1	
EP34-12	12	34	31	25.5	24.5	20.5	17	181	181	199	165	11.5
EP84-12	12	84	76.5	63	60.5	50.5	30	235	235	407	173	29.2
EP130-12	12	130	118	97.5	93.6	78	65	239	239	452	172	39.8
EP160-12	12	160	145	120	115	96	80	240	240	557	172	48.9



Nishant Power Solutions Pvt. Ltd.

5-54 4B, High Street Corporate Centre,
Kapurbawadi, Thane (W) MS India 400601

Tel : +91 22 25404025 / Cell 9820843000

Email : sales@upsbatteries.co.in Visit at : www.upsbatteries.co.in